

# TYPE APPROVAL CERTIFICATE

Certificate no.:  
**TAA00000YU**  
Revision No:  
**6**

## This is to certify:

that the **Remote Control System Steering Gear**

with type designation(s)  
**NAVIGUIDE 4000**

issued to

**Sperry Marine B.V. - German Branch**  
**Hamburg, Germany**

is found to comply with

**IMO Res. A.694(17) General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids**

## Application:

**Product(s) approved by this certificate fulfill(s) minimum performance requirements for electronic shipborne navigational aids and all other bridge-mounted equipment as given in IMO Resolution A.694(17).**

Issued at **Hamburg** on **2023-07-29**

for **DNV**

This Certificate is valid until **2025-01-31**.

DNV local unit: **Hamburg**

Approval Engineer: **Jörg Rebel**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

The NAVIGUIDE 4000 Manual Steering System based on the NAVINET 4000 Steering Control Network may consist of the following equipment:

<i>Description</i>	<i>P/N</i>
Steering Control Unit and Software 020801-0000-000 Rev.: x	074851-0000-xxx
Output Boards: DC Solenoid Board for On/Off solenoid valves	020040-0000-xxx, or 020041-0000-xxx
AC Solenoid Board for On/Off solenoid valves	020042-0000-xxx, or 020043-0000-xxx
Isolated Proportional Output Board $\pm 10$ V or 4..20 mA	020044-0000-xxx
SyncroHelm FU Handwheel - $\pm 45^\circ$ , with 3 potentiometers - $\pm 45^\circ$ , with 6 potentiometers - $\pm 70^\circ$ , with 6 potentiometers	074741-0000-xxx, or 074817-0000-xxx, or 074818-0000-xxx
FU-Miniwheel and Display Unit and Software 020238-0000-000 Rev.: x	074691-0000-xxx
SyncroHelm FU-Miniwheel and Display Unit and Software 020238-0000-000 Rev.: x	074692-0000-xxx
Bus Interface Control Unit (6 Keys) with following functions: Steering Mode Selector, Steering Position Selector, Dual Rudder Sync/Indep. Selector, Steering Alarm Indicator, Setup Unit and Software 020238-0000-000 Rev.: x	074687-0000-xxx
Bus Interface Control Unit (3 Keys) with following functions: Wheel Control Unit, FU Device Interface / Display Unit and Software 020238-0000-000 Rev.: x	074709-0000-xxx
Override Unit	074783-0000-xxx
FU Handwheel for rudder angles up to $35^\circ$ - with 2 potentiometers - with 3 potentiometers - with 4 potentiometers - with 6 potentiometers	074889-0000-xxx 074890-0000-xxx 074891-0000-xxx 074892-0000-xxx
FU Handwheel for rudder angles up to $45^\circ$ - with 1 potentiometer - with 2 potentiometers - with 3 potentiometers - with 4 potentiometers - with 6 potentiometers	074670-0000-xxx 074694-0000-xxx 074755-0000-xxx 074756-0000-xxx 074802-0000-xxx
FU Handwheel for rudder angles up to $70^\circ$ - with 1 potentiometer - with 2 potentiometers - with 3 potentiometers - with 4 potentiometers - with 6 potentiometers	074697-0000-xxx 074698-0000-xxx 074757-0000-xxx 074758-0000-xxx 074781-0000-xxx
FU Miniwheel for rudder angles up to $45^\circ$ , 2 potentiometers FU Miniwheel for rudder angles up to $70^\circ$ , 2 potentiometers	074733-0000-xxx 074739-0000-xxx
NFU Tiller - for two steering gear pumps - for four steering gear pumps - for two steering gear pumps, with protection against unintended use - for four steering gear pumps, with protection against unintended use	074753-0000-xxx 074853-0000-xxx 074754-0000-xxx 074855-0000-xxx
Selector Switch, 8 layers, 4 positions Selector Switch, 12 layers, 8 positions Selector Switch, 20 layers, 8 positions	074205-0000-xxx 074832-0000-xxx 074852-0000-xxx

FU amplifier	060197-0000-xxx
Feedback Unit for rudder angles up to $\pm 45^\circ$ :	
- with 1 potentiometer, one set of limit switches	074720-0000-xxx
- with 1 potentiometer, one set of limit switches, one rudder midship switch	074721-0000-xxx
- with 1 potentiometer, two sets of limit switches, one rudder midship switch	074795-0000-xxx
- with 2 potentiometer, one set of limit switches	074722-0000-xxx
- with 2 potentiometer, two set of limit switches, one rudder midship switch	074796-0000-xxx
- with 3 potentiometer, two set of limit switches, one rudder midship switch	074788-0000-xxx
- with 4 potentiometer, two set of limit switches, one rudder midship switch	074784-0000-xxx
Feedback Unit for rudder angles up to $\pm 70^\circ$ :	
- with 1 potentiometer, one set of limit switches	074724-0000-xxx
- with 2 potentiometer, one set of limit switches	074725-0000-xxx
- with 3 potentiometer, two set of limit switches, one rudder midship switch	074791-0000-xxx
- with 4 potentiometer, two set of limit switches, one rudder midship switch	074785-0000-xxx
Limit Switch Unit	074723-0000-xxx
All Feedback Units / Limit Switch Unit Temperature: A, Vibration: B	
Lever linkage for Feedback Units / Limit Switch Unit:	
- with a maximum length of 350/1200 mm	020508-0000-xxx
- with a maximum length of 600/1500 mm	022051-0000-xxx
Emergency Dual NFU Control Box	074479-0000-xxx
Power Supply Unit	
- input 380/440 V AC, output 24 V DC, 3A	060208-0000-xxx
- input 440 V AC, output 24 V DC, 10 A	060281-0000-xxx
- input 115 V AC, output 24 V DC, 10 A	060290-0000-xxx
- input 230/400 V AC, output 24 V DC, 10 A	060272-0000-xxx
- input 690 V AC, output 24 V DC, 10 A	047891-0000-xxx
Relays	044744-0000-xxx
	047276-0000-xxx
	046154-0000-xxx
	046104-0000-xxx
Diode Board	046673-0000-xxx
Relay Box	074736-0000-xxx

### Application/Limitation

None

### Type Approval documentation

NAVIGUIDE 4000 - Overview Test Reports 20230908.

### Tests carried out

Applicable tests according to IEC/EN 60945 (2002) including Corrigendum 1 (2008) and IACS UR E25, Rev.2 (2022).

### Marking of product

- Components are marked with product name and product number as listed in the table above.
- Basic software version is displayed in the system graphical user interface.
- Each project application configuration is documented in a dedicated version log file which is specific for each vessel.

### Periodical assessment

This certificate is only valid if required periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in <https://approvalfinder.dnv.com>

END OF CERTIFICATE